



SHIN-ETSU

Basic Oil-based Mold Release Agent

“Resiner #10”

Mainly used for :

Vibrational compaction Products

Features :

1. Less bubbles on a product
2. Less stains transferred onto a product

Main component & Property :

1. Brownish-red oil-based liquid
2. Mineral oil & special additives as main ingredients

How to Use :

1. Dilute by adding 1 to 2 parts of kerosene or light oil to 1 part of #10, and stir adequately.
 - The dilution ratio may need to be changed depending on your conditions especially regarding vibration.
2. Apply the diluted #10 to a mold with spray or soft cloth/brush or sponge.
3. Too much application tends to cause adverse effects such as bitten surface, stains and oil bubbles on your concrete product.
4. If a mold is exposed to direct sunshine for a couple of days subsequent to the application, which may cause negative influences on a product such as stains etc.

Remarks :

1. Please refrain from storage under direct sunshine.
2. Be careful about rainwater intrusion.

Size Variations :

1. 200L Drum
2. 18L Square Can

* Sample is available. Please ask the person in charge for details.

*** Contact Information**

SHIN-ETSU Industry Co., Ltd.

Mr.Takafumi Nagasaka/Sales Division

Email nagasaka@shin-etsu.co.jp

Phone +81-48-812-1160

Mobile +81-80-2241-9401

Address 1-52-10, Akabane, Kita-ku, TOKYO

115-0045, JAPAN

