



SHIN-ETSU

Less bubbles & Good Release Power

Oil-based Mold Release Agent

# “Resiner #15”

## **Mainly used for :**

1. Vibrational compaction Products
2. Immediate Demolding Products

## **Features :**

1. Strengthen mold release power
2. Less remnants left on a mold

## **Main component & Property :**

1. Oily liquid
2. Mineral oil & special additives as main ingredients

## **How to Use :**

1. Dilute by adding 1 to 2 parts of kerosene or light oil to 1 part of #15, and stir adequately.
  - The dilution ratio may need to be changed depending on your conditions especially regarding vibration.
2. Apply the diluted #15 to a mold with spray or soft cloth/brush or sponge.
3. Too much application tends to cause adverse effects such as bitten surface, stains and oil bubbles on your concrete product.
4. If a mold is exposed to direct sunshine for a couple of days subsequent to the application, which may cause negative influences on a product such as stains etc.

## **Remarks :**

1. Please refrain from storage under direct sunshine.
2. Be careful about rainwater intrusion.

## **Size Variations :**

1. 200L Drum
2. 18L Square Can \* Sample is available. Please ask the person in charge for details.

### **\* Contact Information**

**SHIN-ETSU Industry Co., Ltd.**

**Mr.Takafumi Nagasaka/Sales Division**

**Email [nagasaka@shin-etsu.co.jp](mailto:nagasaka@shin-etsu.co.jp)**

**Phone +81-48-812-1160**

**Mobile +81-80-2241-9401**

**Address 1-52-10, Akabane, Kita-ku, TOKYO**

**115-0045, JAPAN**



**信越産業株式会社**  
SHIN-ETSU INDUSTRY CO., LTD.