



SHIN-ETSU

## Multi-purpose Oil-base Mold Release Agent

# “Resiner #50”

### **Mainly used for :**

1. Vibrational compaction Products
2. ALC Products
3. As release reinforcing agent mixed in other mold release agents
4. Severe production conditions

### **Features :**

1. White-oriented surface of concrete products
2. #50 can exert great performance even in dilution ratio 1:5 or more.
3. High-viscosity
4. #50 itself can be used as an additive in order for mold release power to be reinforced.

### **Main component & Property :**

1. Yellow-brown oil-based liquid
2. Mineral oil & special additives as main ingredients

### **How to Use :**

Application method and dilution ratio should be changed depending on what purpose #50 is used for. Please ask the person in charge described below for details.

### **Remarks :**

1. Please refrain from storage under direct sunshine.
2. Be careful about rainwater intrusion.

### **Size Variations :**

1. 200L Drum
2. 18L Square Can

\* Sample is available. Please contact the person in charge below for details.

### **\* Contact Information**

**SHIN-ETSU Industry Co., Ltd.**

**Mr.Takafumi Nagasaka/Sales Division**

**Email [nagasaka@shin-etsu.co.jp](mailto:nagasaka@shin-etsu.co.jp)**

**Phone +81-48-812-1160**

**Mobile +81-80-2241-9401**

**Address 1-52-10, Akabane, Kita-ku, TOKYO**

**115-0045, JAPAN**



**信越産業株式会社**  
SHIN-ETSU INDUSTRY CO., LTD.