



SHIN-ETSU

Less-bubbles & High Release Power
Water-soluble Mold Release Agent

“SHIN-ETSU W-21”

Mainly used for :

All vibrational compaction products

Features :

1. High release power
2. Less air bubbles
3. Not only such high performance but Remarkable cost-effectiveness because of water dilution
4. Even less smelly compared with oil-base agents

Main component & Property :

1. Mineral oil, Special additives, Surfactant agent as main ingredients
2. Undiluted solution is oily liquid.

How to Use :

1. Dilute by adding 2 to 6 parts of water to 1 part of “SHIN-ETSU W-21”, and stir adequately.
 - The dilution ratio may need to be changed depending on your conditions especially regarding vibration.
2. Apply the diluted “SHIN-ETSU W-21” to a mold with spray or soft cloth/brush or sponge.
 - “SHIN-ETSU W-21” can exert its performance by water’s drying up after the application.
3. If a mold is exposed to direct sunshine for more than 1 day subsequent to the application, which may cause negative influences on a product such as stains etc.
4. Please dilute only One(1) day portion every single day because the diluted liquid is supposed to be separated afterwards.

Remarks :

1. Please refrain from storage under direct sunshine.
2. Be careful about rainwater intrusion into a drum.

Size Variations :

1. 200L Drum
2. 18L Square Can * Sample is available. Please ask the person in charge below for details.

*** Contact Information**

SHIN-ETSU Industry Co., Ltd.

Mr.Takafumi Nagasaka/Sales Division

Email nagasaka@shin-etsu.co.jp

Phone +81-48-812-1160

Mobile +81-80-2241-9401

Address 1-52-10, Akabane, Kita-ku, TOKYO

115-0045, JAPAN



信越産業株式会社
SHIN-ETSU INDUSTRY CO., LTD.